



Powered by **Sterilight**



Powered by **Sterilight**



Powered by **Sterilight**

- High commercial flow, multi-lamp UV disinfection system with 3" flanges
- Separate control panel with high visibility components
- Recommended for flow rates up to 170 gpm (640 lpm) and available with UV sensor (SHFM-140 - Professional Plus section)


- High commercial flow, multi-lamp UV disinfection system with 3" flanges
- Separate control panel with high visibility components
- Recommended for flow rates up to 210 gpm (790 lpm) and available with UV sensor (SHFM-180 - Professional Plus section)

- High commercial flow, multi-lamp UV disinfection system with 4" flanges
- Separate control panel with high visibility components
- Recommended for flow rates up to 290 gpm (1098 lpm) and available with UV sensor (SHFM-290 - Professional Plus section)

PART NUMBERS			
N. America (NEMA 5-15P)	SHF-140	SHF-180	SHF-290
EU CEE (CEE 7/7)	SHF-140/2	SHF-180/2	SHF-290/2
AUS/NZ (AS 3112)	SHF-140/2A	SHF-180/2A	SHF-290/2A
UK (BS 1363)	SHF-140/2B	SHF-180/2B	SHF-290/2B
DISINFECTION FLOW RATES			
Flow rates based on 95% UVT water (70% UVT for NSF 55 certified systems)			
16 mJ/cm ²	310 GPM (1170 lpm) (70 m ³ /hr)	350 GPM (1300 lpm) (78 m ³ /hr)	543 GPM (2055 lpm) (123 m ³ /hr)
30 mJ/cm ²	170 GPM (640 lpm) (38 m ³ /hr)	210 GPM (790 lpm) (47 m ³ /hr)	290 GPM (1098 lpm) (65 m ³ /hr)
40 mJ/cm ²	125 GPM (470 lpm) (28 m ³ /hr)	160 GPM (600 lpm) (36 m ³ /hr)	215 GPM (813 lpm) (48 m ³ /hr)
SPECIFICATIONS			
Dimensions inch (cm)	34" x 6" x 14" (86.4 cm x 15.2 cm x 35.6 cm)	42 1/2" x 6" x 14" (107.3 cm x 15.2 cm x 35.6 cm)	42 1/2" x 8" x 17" (108 cm x 20.3 cm x 43.5 cm)
Shipping Weight lbs (kg)	68 lbs (30.8 kg)	78 lbs (35.4 kg)	286 lbs (130 kg)
Connection Size	3" FLANGE	3" FLANGE	4" FLANGE
Power Consumption	320W	400W	550W
REPLACEMENT PARTS			
Lamp/Quartz Sleeve Kit	QL-140 (Quantity 4)	QL-180 (Quantity 4)	QL-290 (Quantity 5)
UV Lamp Only	S740RL-4C (Quantity 4)	S950RL-4C (Quantity 4)	S950RL-4C (Quantity 5)
Quartz Sleeve Only	QS-012 (Quantity 4)	QS-180 (Quantity 4)	QSO-950 (Quantity 5)
Controller	BA-ICE-HF (Quantity 4)	BA-ICE-HF (Quantity 4)	BA-ICE-HF (Quantity 5)



Phone: (+84) 98 228 3389
 Website: <https://moitruongcuulong.com/>
 Email: ctmoitruongcuulong@gmail.com





2024 CATALOGUE

2024 CATALOGUE



VIQUA

MST: 0318 391 771

Hotline: +84 98-228-3389

CÔNG TY TNHH THIẾT BỊ ĐIỆN & MÔI TRƯỜNG CỨU LONG

Số tài khoản: 8093 6688 tại Ngân hàng TMCP Á Châu (ACB) - PGD Gò Vấp

Web: <https://clfvietnam.com> <https://ocnuocculong.com> <https://moitruongculong.com>
Email: VietNamCLF@gmail.com Culongfilter@gmail.com Ctmoitruongculong@gmail.com

Địa chỉ: 60 Đường 3158A Phạm Thế Hiển, Phường 7, Quận 8, Tp.HCM
Kho: Đường 2F, KCN Vĩnh Lộc, X. Vĩnh Lộc A, H. Bình Chánh, Tp.HCM
Xưởng: Đường Liên ấp 234, xã Vĩnh Lộc A, huyện Bình Chánh, Tp.HCM

VIQUA



CÔNG TY TNHH THIẾT BỊ ĐIỆN & MÔI TRƯỜNG CỨU LONG
MST: 0318 391 771



CUNG CẤP

THIẾT BỊ - VẬT TƯ XỬ LÝ NƯỚC



<https://clfvietnam.com>
<https://ocnuocculong.com>
<https://moitruongculong.com>

2024



MÔI TRƯỜNG CỨU LONG
Đang chờ anh chị đặt mua



<https://clfvietnam.com>
<https://ocnuocculong.com>
<https://moitruongculong.com>

2024