

Large Commercial Reverse Osmosis Elements

DuPont Water Solutions launched first TapTec™ Large commercial reverse osmosis (RO) Elements to address the strong demand in the large commercial industry for affordable, reliable and technology-proven RO elements. DuPont*TapTec* LC HF 4040 is the best option for large commercial applications like water refilling stations, food service and restaurants, hotels and resorts, water vending, health care facilities, science laboratories, marinas and yachts and many more.



TapTec LC HF 4040 Large Commercial Reverse Osmosis Elements



Ultra-high Permeate Flow at 2800 gallon per day



Value for money, affordable price with excellent quality

Quick stabilization



DuPont* TapTec™, powered by more than 40 years of membrane innovation

Product Parameters

Product	Length (inches)	Diameter (inches)	Permeate Flow Rate (gpd)	Min. Salt Rejection (%)	Stabilized Salt Rejection (%)
LC HF-4040	40	3.9	2800	98.5	99

1. Permeate flow and salt rejection based on the following test conditions: 1500 ppm NaCl, 77°F (25°C), 15% recovery, pH 7, and applied pressure J50psig.
2. Permeate flows for individual elements may vary +/-15%.
3. For the purpose of improvement, specifications may be updated periodically.

Worldwide Certifications



Certified to
NSF/ANSI/CAN 61



Hotline: +84 98 228 338 9
Website: <https://locnuoccuulong.com/>



Have a question? Contact us at: www.dupont.com/water/contact-us



All information set forth herein is for informational purposes only. This information is general information and may differ from what is based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. **NOWARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY DISCLAIMED.** No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

© 2022 DuPont. DuPont®, the DuPont Oval Logo, and all trademarks and service marks denoted with "™", "®" or "®" are owned by affiliates of DuPont de Nemours Inc., unless otherwise noted.

45-D03665-en-0922 CDP